

VTM-LED170P / 190P

17" & 19" Professional LED Monitors with HDMI, VGA, and Dual Looping BNC's



FEATURES

- 17" / 19" LED Display Panel
- Professional grade display designed for 24/7 continuous use in security applications
- HDMI, VGA, and Dual Looping BNC Composite Video Inputs & Stereo Audio Input
- Resolution up to 1280 x 1024 (SXGA)
- Contrast Ratio of 10,000:1
- Ultra High Dynamic Contrast provides more accurate colors
- 3D comb filter ensures clear contour lines of the image
- <5ms Response time
- 170° Horizontal Viewing Angle
- Picture In Picture (PIP) / POP (Picture On Picture) Display Options
- Front Panel Controls
- VESA 75mm Standard Mounting
- 50,000 Hour Panel Life
- Rack Mountable with optional VI-LED17RM / VI-LED19RM Rack Kit
- Mercury-Free



VTM-LED170P / VTM-LED190P Rear Connections



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VTM-LED170P / 190P

17" & 19" Professional LED Monitors with HDMI, VGA, and Dual Looping BNC's

Detailed Specifications	VTM-LED170P	VTM-LED190P
Screen Size	17"	19"
Display Type	LED	
Aspect Ratio	4:3	
Resolution	SXGA (1280x1024)	
Response Time	<5ms	
Contrast Ratio	10,000:1	
Display Color	16.7 Million	
Brightness	300cd/m ²	
Pixel Type	Active Matrix TFT	
Pixel Pitch	0.264(H) x 0.264(V)	0.294(H) x 0.294(V)
Viewing Angle (H/V)	170° / 160°	
Video System	NTSC/PAL	
Video In/Out	2 BNC Inputs / 2 BNC Outputs (Looping)	
VGA In	1 (15Pin D-Sub)	
HDMI In	1	
Audio Input	Stereo RCA & 1/8" PC	
Built In speaker	Yes (1.5W x 2)	
PIP / POP	Analog / Digital	
Remote	NO	
3D Comb Filter	YES	
3D De-Interlace	YES	
Noise Reduction	YES	
Multi-Language	English, Spanish, German, French, Italian, Russia, Turkish, Japanese, Polish	
Stand Tilt	-5° ~ 15°	
Vesa Mount Size	75mm x 75mm	
Power Adapter	12VDC (AC100/240 [50/60])	
Power Consumption	20W Max	25W Max
Certifications	UL, FCC-DOC, CE, ROHS	
Operating Temperature	32° to 104° F (0° to 40° C)	
Operating Humidity	10% to 90% relative, non-condensing	
Dimensions (w/Stand)	15.16" x 15.12" x 6.50" (385 x 384 x 165mm)	16.69" x 16.34" x 6.50" (424 x 415 x 165mm)
Weight	6.98 lbs (3.17kgs)	7.09 lbs (3.22kgs)

